

# HYDROLOCK RAIL

## TITANTECH®

For developers of brownfield and contaminated sites the TITANTECH® family of products represent a major step forward in safeguarding projects against gaseous and chemical contamination.

## JUTA UK

For additional information or assistance, please contact JUTA UK directly.

**HYDROLOCK RAIL** - is a galvanised steel wire mesh specifically designed for use with **HYDROLOCK STRIP**. **HYDROLOCK RAIL** is used to prevent displacement of the strip during concrete pouring. Supplied at 30 mm width in lengths of 1.0 m.

### Application

**HYDROLOCK RAIL** is applied to the surface of the **HYDROLOCK STRIP** post placement, and fixed in place using steel pins/nails at a minimum 300 mm spacing.

### Storage

**HYDROLOCK RAIL** is delivered in lengths of 1.0 m in a box containing 30 units. Boxes should be stacked no more than 5 high. Shelf life is unlimited.

### Accessory Products

**HYDROLOCK RAIL** is an accessory product to **HYDROLOCK** to assist with jointing and sealing. Additional accessories include:

- **HYDROLOCK STRIP**
- **HYDROLOCK GRANULES**
- **HYDROLOCK PASTE**

<b>Material</b>	Galvanised Steel
<b>Width</b>	30 mm
<b>Length</b>	1.0 m

### Named Accessory in Certification



Please Scan



Rev 2024